



LABEL SLITTER



SPECIFICATIONS

Electrical Features

- 4 Blades included
- 3" fixed core holders
- Outside roll diameter up to 250mm
- Media width up to 220mm
- Minimum slitting width 22mm
- Manual speed adjustment
- Label Rewinding face-out or face-in

Dimensions

L: 820mm
H: 400mm
W: 460mm
Weight: 25kg

- > **External auto-switching 100/240V power supply**
- > **Equipped with 3" fixed core holder**
- > **Can use the splitter "on-line" with your label printer**
- > **Possible to obtain rows of labels not narrower than 22mm**
- > **Easy to Use**

The longitudinal label splitter satisfies the present-day necessity to make the most of the print area with the possibility to obtain more rows of labels from the same roll, and then split it through the use of the splitter.

The cutting operations are done by a common cutter blade that is located in an opposite blade holder. The splitter has an external auto-switching 100/240VAC - 5A at 24V power supply and an electronic circuit controls all its functions. The new splitter, equipped with two 76mm (3") fixed core holders, is able to work rolls with a diameter of 250mm. The maximum width of the roll is 220mm and it is possible to obtain rows of labels not narrower than 22mm.

CONTACT US NOW TO SEE THEM IN ACTION OR FOR SAMPLES & COSTINGS



p 1800 113 904 **f** 07 3273 5596 **e** sales@labelprintsystem.com.au

Head Office PO Box 512 Acacia Ridge LPO QLD 4110

Showroom Unit 3/13 Murdoch Circuit Acacia Ridge QLD 4110

ABN 52 010 815 086

digital printers thermal printers labels support

labelprintsystems.com.au